

Listing of Claims:

1. (Previously Presented) An apparatus comprising:
a link quality estimation unit operative to generate a link quality estimation in response to a forward link power control instruction received on a forward link common channel; and
a power control unit coupled to the link quality estimation unit, the power control unit operative to generate a reverse link power control instruction in response to the link quality estimation,
wherein the reverse link power control instruction includes one or more commands configured to adjust a transmit power of the forward link at a base station.

2. (Previously Presented) The apparatus of claim 1, wherein the apparatus controls transmission power of the reverse link power control instruction on a reverse link in response to the forward link power control instruction.

3. (Previously Presented) The apparatus of claim 1, wherein the apparatus transmits the reverse link power control instruction on a reverse link.

4. (Previously Presented) An apparatus comprising:
a determination unit operative to determine a reverse link power control instruction received on a reverse link for base station transmission on a forward link;
an adjustment unit coupled to the determination unit, the adjustment unit operative to adjust a transmission power level of a forward link power control instruction based on the reverse link power control instruction; and
a transmitter operative to transmit the forward link power control instruction on a forward link common channel.

5-10. (Cancelled)

11. (Previously Presented) The apparatus of claim 4, wherein the transmission power level of the forward link power control instruction is initially set to a reference value.

12. (Previously Presented) The apparatus of claim 1, wherein the link quality estimation is a SNR.

13. (Previously Presented) A method for power control in a wireless communication system, the method comprising:

generating a link quality estimation in response to a forward link power control instruction received on a forward link common channel; and

generating a reverse link power control instruction in response to the link quality estimation,

wherein the reverse link power control instruction includes one or more commands configured to adjust a transmit power of the forward link at a base station.

14. (Previously Presented) The method of claim 13, further comprising controlling transmission power of the reverse link in response to the forward link power control instruction.

15. (Previously Presented) The method of claim 13, further comprising transmitting the reverse link power control instruction on the reverse link.

16. (Previously Presented) The method of claim 13, wherein the link quality estimation is a SNR.

17. (Previously Presented) A method for power control in a wireless communication system, the method comprising:

determining a reverse link power control instruction received on a reverse link for base station transmission on a forward link;

adjusting a transmission power level of a forward link power control instruction based on the reverse link power control instruction; and

transmitting the forward link power control instruction on a forward link common channel.

18. (Previously Presented) The method of claim 17, wherein a transmission power level of the forward link power control instruction is initially set to a reference value.

19. (Previously Presented) An apparatus comprising:
means for generating a link quality estimation in response to a forward link power control instruction received on a forward link common channel; and
means for generating a reverse link power control instruction in response to the link quality estimation,
wherein the reverse link power control instruction includes one or more commands configured to adjust a transmit power of the forward link at a base station.

20. (Previously Presented) The apparatus of claim 19, further comprising means for controlling transmission power of the reverse link power control instruction on a reverse link in response to the forward link power control instruction.

21. (Previously Presented) The apparatus of claim 19, further comprising means for transmitting the reverse link power control instruction on a reverse link.

22. (Previously Presented) The apparatus of claim 19, wherein the link quality estimation is a SNR.

23. (Previously Presented) An apparatus comprising:
means for determining a reverse link power control instruction received on a reverse link for base station transmission on a forward link;
means for adjusting a transmission power level of a forward link power control instruction based on the reverse link power control instruction,
wherein the means for adjusting are coupled to the means for determining; and

means for transmitting the forward link power control instruction on the forward link common channel.

24. (Previously Presented) The apparatus of claim 23, wherein the transmission power level of the forward link power control instruction is initially set to a reference value.

25. (Previously Presented) A machine-readable medium embodying a method for power control in a remote station apparatus, the method comprising:

generating a link quality estimation in response to a forward link power control instruction received on a forward link common channel; and

generating a reverse link power control instruction in response to the link quality estimation,

wherein the reverse link power control instruction includes one or more commands configured to adjust a transmit power of the forward link at a base station.

26. (Previously Presented) A machine-readable medium embodying a method for power control in a base station apparatus, the method comprising:

determining a reverse link power control instruction received on a reverse link for base station transmission on a forward link;

adjusting a transmission power level of a forward link power control instruction based on the reverse link power control instruction; and

transmitting the forward link power control instruction on a forward link common channel

27. (Cancelled)

28. (Previously Presented) The apparatus of claim 1, wherein the link quality estimation unit is operative to generate the link quality estimation based on a received power level of the forward link power control instruction.

29. (Previously Presented) The apparatus of claim 4, wherein the reverse link power control instruction is extracted from a signal received on the reverse link.

30-32. (Cancelled)

33. (Previously Presented) The method of claim 13, wherein the link quality estimation is generated based on a received power level of the forward link power control instruction.

34. (Previously Presented) The method of claim 17, wherein the determination comprises extracting the reverse link power control instruction from a signal received on the reverse link

35-37. (Cancelled)

38. (Previously Presented) The apparatus of claim 19, wherein the means for generating a link quality estimation unit are for generating the link quality estimation based on a received power level of the forward link power control instruction.

39. (Previously Presented) The apparatus of claim 23, wherein the reverse link power control instruction is extracted from a signal received on the reverse link.

40. and 41. (Cancelled)

42. (Previously Presented) A remote station apparatus, comprising:
a link quality estimation unit operative to generate a link quality estimation in response to a forward link power control instruction received on a forward link common channel;
a power control unit coupled to the link quality estimation unit, the power control unit operative to generate a reverse link power control instruction in response to the link quality estimation; and
one or more antennas configured to receive the forward link power control instruction on

the forward link,

wherein the reverse link power control instruction includes one or more commands configured to adjust a transmit power of the forward link at a base station.

43. (Previously Presented) A base station apparatus, comprising:
- a determination unit operative to determine a reverse link power control instruction received on a reverse link for base station transmission on a forward link;
 - an adjustment unit coupled to the determination unit, the adjustment unit operative to adjust a transmission power level of a forward link power control instruction based on the reverse link power control instruction;
 - one or more antennas configured to receive the reverse link power control instruction on the reverse link; and
 - a transmitter operative to transmit the forward link power control instruction on a forward link common channel.